

SPEC

Main Specifications

		The new Prius PHV	The new Prius		Conventional Prius PHV
Press release time		2016 autumn	2015 December 9,		January 2012
grade		Over	2WD "S"	E- Four "S"	2WD "S"
Total emission	L	1.797	1.797		1.797
transmission		Electric-type continuously variable transmission	Electric-type continuously variable transmission		Electric-type continuously variable transmission
Drive		2WD (FF)	2WD (FF)	E- Four	2WD (FF)
full length	mm	4,645	4,540		4,480
Full width	mm	1,760	1,760		1,745
Total height	mm	1,470	1,470	1,475	1,490
Wheelbase	mm	2,700	2,700		2,700
Interior length	mm	2,110	2,110		1,905
Interior width	mm	1,490	1,490		1,470
Interior height	mm	1,195	1,195 * 1		1,225
Weight of vehicle	kg	1,510	1,360	1,430	1,410
Riding capacity	Name	Four	Five		Five
Minimum turning radius	m	5.1	5.1		5.2
tire size		195 / 65R15	195 / ⁶⁵ R15 * 2		195 / 65R15

Main specifications of the engine / motor

	The new Prius PHV	The new Prius		Conventional Prius PHV
grade	Over	2WD "S"	E- Four "S"	2WD "S"
Engine Type	Series four-cylinder DOHC	Series four-cylinder DOHC		Series four-cylinder DOHC
Engine model	2ZR-FXE	2ZR-FXE		2ZR-FXE
Total emission L	1.797	1.797		1.797
Maximum output of <net> kW (PS) / rpm	72 (98) / 5,200	72 (98) / 5,200		73 (99) / 5,200
Maximum torque <net> N · m (kgf · m) / rpm	142 (14.5) / 3,600	142 (14.5) / 3,600		142 (14.5) / 4,000
Motor Model	1NM / 1SM	1NM		3JM
Maximum output kW (PS)	53 (72) / 23 (31)	53 (72)		60 (82)
Maximum torque N · m (kgf · m)	163 (16.6) / 40 (4.1)	163 (16.6)		207 (21.1)
System maximum output * 3 kW (PS)	90 (122)	90 (122)		100 (136)
JC08 mode running fuel consumption km / L	Over	37.2	34.0	-
JC08 mode running hybrid fuel economy km / L	37 * 4	-		31.6
EV running in terms of distance * 5 km	More than 60	-		26.4

Aerodynamics

	The new Prius PHV	The new Prius
C D value	0.25 * 6	0.24 * 6

TOYOTA Web Passportのメールマガジンで「新型プリウスPHV」をはじめ、TOYOTAの最新情報をお届け

入力は簡単。3項目のみ。

→ 登録する

既に会員の方は、MY TOYOTA にログイン後、メールマガジンの設定をご確認ください。

→ ログイン

* 1 Tilt and slide electric moon roof equipped car is 1,145mm.

* 2 "Touring Selection" is 215 / 45R17.

* 3 By the engine and the motor, it can be exhibited as a power performance output. Internal calculation value.

* 4 Development target value.

* FiveA distance corresponding to the travel using only the power by external charging.

* 6 House measurements.

■ Such as numeric, specifications are those under consideration, you might want to change.



→ 災害時、地域社会のためにクルマができること



→ PHV Drive Support

PHV Drive Supportは従来型プリウスPHV（2012年発売モデル）のサービスです。
新型プリウスPHVのサービスではありません。

→ **トヨタWEBサイト ご利用者アンケート**
毎月抽選で500円分のギフト券プレゼント