Part Number: Mounting Kit PT296-47120

Extension Assembly Kit Contents

Item #	Quantity Reqd.	Description
1	1	Extension Box (w/BT wire
		harness)

Mounting Kit Contents

Item #	Quantity Reqd.	Description	
2	4	M8 Screws	
3	1	Wire harness, Jumper Cable	

Hardware Bag Contents – 1

Item #	Quantity Reqd.	Description
1	4	Screws (M8)

Additional Items Required For Installation

Item #	Quantity Reqd.	Description
1	1	USB Memory Stick

Conflicts

Premium	AVN	Audio
---------	-----	-------

Recommended Tools

Personal & Vehicle	Notes	
Protection		
Seat Covers		
Floor Protectors		
Special Tools	Notes	
Installation Tools	Notes	
Ratchet		
Extensions		
Sockets	8 mm,10mm	
Wrench	10mm	
Nylon Made Panel Removal	e.g. Panel Pry Tool #1	
Tool	Toyota SST # 00002-06001-01	
Masking Tape	(1-2" wide)	
Protective Cloth		
Special Chemicals	Notes	
Cleaner	VDC Approved Cleaner	

NOTE: Part number of this accessory may not be the same as the part number shown.

General Applicability

Recommended Sequence of Application

Item # Accessory

*Mandatory

Vehicle Service Parts (may be required for reassembly)

Item #	Quantity Reqd.	Description

Legend

STOP	<u>STOP</u> : Damage to the vehicle may occur. Do not proceed until process has been complied with.
÷	<u>OPERATOR SAFETY:</u> Use caution to avoid risk of injury.
	<u>CAUTION</u> : A process that must be carefully observed in order to reduce the risk of damage to the accessory/vehicle and to ensure a quality installation.
ala	TOOLS & EQUIPMENT: Used in Figures calls out the specific tools and equipment recommended for this process.
	<u>REVISION MARK:</u> This mark highlights a change in installation with respect to previous issue.
V	<u>SAFETY TORQUE</u> : This mark indicates that torque is related to safety.

Issue: D 04/18/2012

Parts Description of Radio Extension Box

		1	
Item #	Parts Name	Parts No.	Qty
1	Extension Box	86100 VV050	1

Parts Description of Mounting Kit



Item #	Parts Name	Qty
1	Jumper Cable	1
2	M8 Screws	4

ТОУОТА

Procedure

Care must be taken when installing this accessory to ensure damage does not occur to the vehicle. The installation of this accessory should follow approved guidelines to ensure a quality installation.

These guidelines can be found in the "Accessory Installation Practices" document.

This document covers such items as:-

- Vehicle Protection (use of covers and blankets, cleaning chemicals, etc.).
- Safety (eye protection, rechecking torque procedure, etc.).
- Vehicle Disassembly/Reassembly (panel removal, part storage, etc.).
- Electrical Component Disassembly/Reassembly (battery disconnection, connector removal, etc.).

Please see your Toyota dealer for a copy of this document.



Place all removed parts on a protected surface.

Connectors: -

When disconnecting connectors, do not pull on the wires; pull on the connector





Vehicle Protection.

(a) Remove rear floor cover

(1) Protect the bumper before starting.

2. Vehicle Disassembly

(a) Remove rear deck board. Fig. 2-1

Procedure







(c) Remove small tray rear passenger-side covering battery. Fig. 2-3

(d) Disconnect negative battery cable using 10mm wrench (do not touch positive terminal with any tool when removing cable). Fig. 2-4

- (e) Open upper and lower glove box.
- (f) Pullout upper storage compartment with hands only (no tools needed.) Fig. 2-5

Issue: D 04/18/2012

Procedure



- (g) Place protective tape on dash.
- (h) Insert pry tool and slowly open top. Fig 2-6

- (i) Remove bottom of ignition panel with hands (pry tool not needed). Fig. 2-7
- (j) Unplug electrical connections.

(k) Remove air conditioning/vent cover by hand pulling rearwards. Fig. 2-8

Remove (4) 10mm hex screws attaching radio. Fig. 2.9

Procedure



- (m)Cover lower AC cover control panel with a protective cloth.
 - (n) Remove Display Audio radio. Fig. 2-10



(o) Disconnect connections at back of radio. Fig. 2-11





(p) Remove white tape from Bluetooth/USB harness. Fig. 2-12

ТОУОТА

Procedure





3. Installing Extension Box

- (a) Remove break-away tape from Bluetooth/USB on Extension Box cable.
- (b) Plug Bluetooth connector from Extension box into radio. Fig. 3-1

(c) Install (4) Extension Box mounting screws (2-on each side). Fig. 3-2

Procedure



(d) Attach jumper cable (Included in Extension Box kit). Fig. 3-3



 (e) Locate the GPS antenna connector.
Reconnect all cables, including new Bluetooth and jumper cable on Extension Box and GPS connector. Fig. 3-4 Procedure



- 4. **Re-install Display Audio Radio & Function** Check
- (a) Reconnect battery, torque to 48 inch/lbs and conduct in-process functional check.
- (b) Press the Setup button on the faceplate. Fig. 4-1



- (c) Diagnostic Mode Checks
- (d) Press CAR button, hold, and cycle lights three times. Fig. 4-1
- (e) Touch Function Check/Setting. Fig. 4-2



(f) Touch Ext Box. Fig. 4-3

Procedure







(g) Touch Diagnostics. Fig. 4-4

- (h) Plug USB device into vehicle. Fig. 4-5
- (i) Confirm Diagnostics Test results. Fig. 4-6
 - Bluetooth Antenna Connected: Yes
 - FM Harness Connected: No
 - GPS Antenna Connected: Yes
 - USB Connected: Yes

- (j) Exit diagnostics mode by holding down the **SETUP** button
- (k) Function check AM, FM, XM, APPS, CAR, MAP, Km/h-MPH, Hazard Warning Light (note: "FM Harness Connected" will read "No")

Procedure

Vehicle Functional Check				
	AM Radio	AM Radio Signal/Change Stations		
	FM Radio	FM Radio Signal/Change Stations		
	XM Radio	XM Radio Signal/Change Stations		
	Steering Wheel Controls	All Steering Wheel Controls Functional		
	Backup Camera	Backup Camera Functional		
	APPs	Applications Displayed/Functional		
	CAR	CAR Button Functional		
	МАР	MAP Button Functional		
	Km/h-MPH	Km/h-MPH Settings Change		
	Hazard Warning Lights	Hazard Lights Function		