

THANK YOU FOR YOUR ORDER.

We're now processing your order. You will receive an email confirmation shortly.
Please print this page or write down your order number (see below).

Order #: 263702

Payment Method: Real-time Credit Card (- authorizenet)

Shipping Method: FedEx Ground

Email Address: [REDACTED]

Shipping Address

Billing Address

Description

Quantity

Price

2004-2009 Toyota Prius - "NO-DRILL" Class 3 Trailer Hitch Est. Ship Time: 4
to 10 Business Days
MFG: Quality S
Part #: 132

1

~~\$145.95~~
Save: \$21.89

\$124.06
Subtotal:

\$0.00
Sales Tax:

\$19.88
Weight-Based Shipping:

\$143.94
Total:



132

RECEIVER HITCH

Toyota Prius

2004 & Up

INSTALLATION INSTRUCTIONS

1. **Check** all parts. **Read and understand** instructions completely before beginning installation.

1) Hitch

4) 10mm -1.25 x 40mm **Hex Bolts**

4) 1/2" **HD Flatwasher**

4) 10mm **Lock Washers**

2. **Remove** the plastic underbody panel on the driver side.

Remove the tow hooks and return them to the customer.

3. **Clean** the under side of the frame rails. Make sure the 10mm -1.25 x 40 bolts screw into the four weld nuts easily. If the bolts show some resistance, clean the threads. The best way to clean the threads is to run a 10mm - 1.25 tap carefully into each weld nut.

4. **Carefully** lift the hitch into position and secure with four 10mm -1.25 x 40mm hex bolts, 10mm lock washers, and HD flatwashers. Snug all the bolts.

5. **Torque** all the 10mm - 1.25 x 40mm bolts to 37 ft/lbs.

6. **You** can reinstall the plastic underbody panel on the driver side with a small modification. With a pair of scissors or sharp knife, enlarge the tow hook slot to the rear of the panel. If you do not wish to do this, return the panel and the fasteners to the customer. With the panel trimmed, reinstall the panel with the existing fasteners.

GROSS LOAD		
HITCH TYPE	MAX. TRL WT (LB)	MAX. TONGUE WT (LB)
Not to be used as a weight distribution Hitch		
WEIGHT CARRYING	2,000	200

Periodically check this receiver hitch to ensure -
that all bolts are tight and all components sound.

The manufacturer warrants this product to be free of defects in material or workmanship at the time of retail purchase by the original purchaser. If the product is found to be defective, the manufacturer may repair or replace the product, at its option, when product is returned, prepaid, with proof of purchase to the manufacturer. Alteration to, misuse of, or improper installation of product voids this warranty. Manufacturer's liability is limited to repair or replacement of products found to be defective, and specifically excludes liability for incidental or consequential loss or damage.

Quality S Manufacturing, Inc., Phoenix, AZ

