
Diagnostic Report

Created by OBDLink - OBD Solutions

www.obdsoftware.net

Date: 21.09.2022 21:07:34

VIN: JTDKN36U5010XXXXX

Manufacturer: Toyota

Model: Prius

Option: 1.5 L

Year: 2009

Monitor Status Report

Name	Continuous	Available	Complete
Misfire	Yes	Yes	Yes
Fuel System	Yes	Yes	Yes
Components	Yes	Yes	Yes
Catalyst	No	Yes	Yes
Heated Catalyst	No	No	No
Evap System	No	No	No
Secondary Air System	No	No	No
AC Refrigerant	No	No	No
Oxygen Sensor	No	Yes	Yes
Oxygen Sensor Heater	No	No	No
EGR System	No	Yes	Yes

MIL Off

Number of Confirmed Codes: 0

Readiness Standard: None

This vehicle is ready for emissions testing.

Trouble Code Report

There are no pending, stored, or permanent diagnostic trouble codes (DTCs).

Mode \$01 - Powertrain Diagnostic Data

PID	Description	Value	Units
SAE 0x03	Fuel system 1 status	1	
SAE 0x03	Fuel system 2 status	0	
SAE 0x04	Calculated load value	0	%
SAE 0x05	Engine coolant temperature	75	°C
SAE 0x06	Short term fuel % trim - Bank 1	0	%
SAE 0x07	Long term fuel % trim - Bank 1	0	%
SAE 0x0B	Intake manifold absolute pressure	99	kPa
SAE 0x0C	Engine RPM	0	RPM
SAE 0x0D	Vehicle speed	0	km/h
SAE 0x0E	Ignition timing advance for #1 cylinder	5	deg
SAE 0x0F	Intake air temperature	38	°C
SAE 0x10	Mass air flow rate	0,18	g/s
SAE 0x11	Absolute throttle position	16,08	%
SAE 0x13	Location of oxygen sensors	3	
SAE 0x15	O2 voltage (Bank 1, Sensor 2)	0	V
SAE 0x15	Short term fuel trim (Bank 1, Sensor 2)	99,219	%
SAE 0x1C	OBD requirements to which vehicle or engine is certified	6	
SAE 0x1F	Time since engine start	0	sec
SAE 0x21	Distance traveled while MIL is activated	0	km
SAE 0x24	O2 sensor lambda (Bank 1, Sensor 1)	1,006	
SAE 0x24	O2 sensor voltage wide range (Bank 1, Sensor 1)	3,337	V
SAE 0x2C	Commanded EGR	0	%
SAE 0x2E	Commanded evaporative purge	0	%
SAE 0x30	Number of warm-ups since DTCs cleared	12	
SAE 0x31	Distance traveled since DTCs cleared	127	km
SAE 0x33	Barometric pressure	93	kPa
SAE 0x34	O2 sensor lambda wide range (current probe) (Bank 1, Sensor 1)	1,006	
SAE 0x34	O2 sensor current wide range (Bank 1, Sensor 1)	0,02	mA
SAE 0x3C	Catalyst temperature (Bank 1 Sensor 1)	503,7	°C
SAE 0x3E	Catalyst temperature (Bank 1 Sensor 2)	436,7	°C
SAE 0x42	Control module voltage	14,65	V
SAE 0x43	Absolute load value	0	%
SAE 0x44	Fuel/Air commanded equivalence ratio	0,94	
SAE 0x45	Relative throttle position	0	%
SAE 0x47	Absolute throttle position B	47,84	%
SAE 0x4C	Commanded throttle actuator control	16,08	%
SAE 0x4D	Engine run time run while MIL is activated	0	min

SAE 0x4E	Engine run time since DTCs cleared	299	min
Aux 0x00	Input voltage read by the scan tool	14,8	V
SAE 0x46	Ambient air temperature	10	°C
SAE 0x49	Accelerator pedal position D	16,08	%
SAE 0x4A	Accelerator pedal position E	32,16	%
SAE 0x5B	Hybrid battery pack remaining life	48,24	%

Mode \$02 - Freeze Frame

Freeze Frame data is not available.

Mode \$05 - Oxygen Sensors

Sensor	Available
Bank 1 - Sensor 1	Yes
Bank 1 - Sensor 2	Yes
Bank 1 - Sensor 3	No
Bank 1 - Sensor 4	No
Bank 2 - Sensor 1	No
Bank 2 - Sensor 2	No
Bank 2 - Sensor 3	No
Bank 2 - Sensor 4	No

Mode \$06 - On-Board Monitoring

Component	Description	Value	Minimum	Maximum	Units	Result
\$01 - Exhaust Gas Sensor Monitor Bank 1 – Sensor 1	TID \$8E - Manufacturer Defined	0,612	0,169	19,898	V	Pass
\$01 - Exhaust Gas Sensor Monitor Bank 1 – Sensor 1	TID \$91 - Manufacturer Defined	2,4414	1,5625	3,5898	mA	Pass
\$02 - Exhaust Gas Sensor Monitor Bank 1 – Sensor 2	TID \$07 - Minimum sensor voltage for test cycle (calculated)	0,136	0	0,214	V	Pass

\$02 - Exhaust Gas Sensor Monitor Bank 1 – Sensor 2	TID \$08 - Maximum sensor voltage for test cycle (calculated)	0,82	0,585	0,995	V	Pass
\$02 - Exhaust Gas Sensor Monitor Bank 1 – Sensor 2	TID \$8F - Manufacturer Defined	0,2592	0	2,0984		Pass
\$21 - Catalyst Monitor Bank 1	TID \$A9 - Manufacturer Defined	0,223	0,2196	9,9939		Pass
\$31 - EGR Monitor Bank 1	TID \$BD - Manufacturer Defined	19,66	0,95	655,35	kPa	Pass
\$A1 - Misfire Monitor General Data	TID \$0B - EWMA (Exponential Weighted Moving Average) misfire counts for last ten (10) driving cycles	0	0	65535	counts	Pass
\$A1 - Misfire Monitor General Data	TID \$0C - Misfire counts for last/current driving cycles (calculated, rounded to an integer value)	1	0	65535	counts	Pass
\$A2 - Misfire Cylinder 1 Data	TID \$0B - EWMA (Exponential Weighted Moving Average) misfire counts for last ten (10) driving cycles	0	0	65535	counts	Pass
\$A2 - Misfire Cylinder 1 Data	TID \$0C - Misfire counts for last/current driving cycles (calculated, rounded to an integer value)	0	0	65535	counts	Pass
\$A3 - Misfire Cylinder 2 Data	TID \$0B - EWMA (Exponential Weighted Moving Average) misfire counts for last ten (10) driving cycles	0	0	65535	counts	Pass
\$A3 - Misfire Cylinder 2 Data	TID \$0C - Misfire counts for last/current driving cycles (calculated, rounded to an integer value)	0	0	65535	counts	Pass
\$A4 - Misfire Cylinder 3 Data	TID \$0B - EWMA (Exponential Weighted Moving Average) misfire counts for last ten (10) driving cycles	0	0	65535	counts	Pass
\$A4 - Misfire Cylinder 3 Data	TID \$0C - Misfire counts for last/current driving cycles (calculated, rounded to an integer value)	0	0	65535	counts	Pass
\$A5 - Misfire Cylinder 4 Data	TID \$0B - EWMA (Exponential Weighted Moving Average) misfire counts for last ten (10) driving cycles	0	0	65535	counts	Pass

	driving cycles					
\$A5 - Misfire Cylinder 4 Data	TID \$0C - Misfire counts for last/current driving cycles (calculated, rounded to an integer value)	1	0	65535	counts	Pass

Mode \$09 - Vehicle Information

General Information

Description	Value
Vehicle Identification Number	JTDKN36U5010XXXXX
Calibration ID - \$7E2	896B34750000
Calibration ID - \$7E2	896B54701100
Calibration ID - \$7E2	898844701400
Calibration ID - \$7E2	898844702300
Calibration ID - \$7E0	34717200
Calibration ID - \$7E0	A4701000
Calibration Verification Number - \$7E2	9C7DCB91
Calibration Verification Number - \$7E2	B5A5D17C
Calibration Verification Number - \$7E2	6D4B0BC4
Calibration Verification Number - \$7E2	2E227B50
Calibration Verification Number - \$7E0	F0A7763F
Calibration Verification Number - \$7E0	611F6EF2