

10/4/2026			Load tested at approx 15A using two 1 ohm 100W resistors in parallel (0.5ohm)								Capacity tested at 2A using charger/Discharger					
Blk	Module	Old posn	OCV	V 0 sec	CurrStart	V 10sec	V 20sec	V 30sec	V 40sec	V 50sec	V 60sec	CurrEnd A	V Diff	mohms	Capacity mAh	Module
10	20	19	8.05	7.81	14.21	7.74	7.68	7.64	7.60	7.57	7.55	12.21	0.26	0.018	5388	20
10	19	20	8.04	7.79	14.31	7.70	7.64	7.59	7.55	7.52	7.50	12.21	0.29	0.020	4709	19
9	18	9	8.08	7.91	14.67	7.83	7.75	7.75	7.72	7.69	7.67	12.37	0.24	0.016	5710	18
9	17	18	8.04	7.81	14.50	7.71	7.66	7.62	7.58	7.54	7.53	12.27	0.28	0.019	5710	17
8	16	7	8.08	7.73	15.00	7.72	7.64	7.59	7.56	7.53	7.49	12.33	0.24	0.016	4701	16
8	15	17	8.06	7.84	14.70	7.75	7.69	7.64	7.60	7.57	7.54	12.20	0.30	0.020	4010	15
7	14	3	8.08	7.85	15.53	7.78	7.71	7.67	7.63	7.60	7.57	12.64	0.28	0.018	4911	14
7	13	12	8.05	7.78	15.65	7.70	7.64	7.59	7.56	7.53	7.50	12.30	0.28	0.018	5953	13
6	12	1	8.09	7.85	15.00	7.77	7.71	7.67	7.64	7.60	7.57	14.00	0.28	0.019	5826	12
6	11	11	8.02	7.80	14.25	7.71	7.64	7.59	7.56	7.52	7.49	12.00	0.31	0.022	5971	11
5	10	10	8.08	7.91	14.38	7.74	7.69	7.64	7.61	7.57	7.54	12.30	0.37	0.026	4904	10
5	9	2	8.08	7.86	15.10	7.77	7.71	7.66	7.62	7.59	7.55	12.60	0.31	0.021	5354	9
4	8	8	8.08	7.79	14.35	7.70	7.63	7.59	7.56	7.52	7.49	12.06	0.30	0.021	4641	8
4	7	13	8.04	7.83	14.73	7.72	7.65	7.61	7.57	7.54	7.51	11.96	0.32	0.022	4834	7
3	6	6	8.08	7.90	14.58	7.76	7.69	7.64	7.60	7.56	7.53	12.19	0.37	0.025	4881	6
3	5	4	8.08	7.84	14.06	7.74	7.67	7.63	7.52	7.49	7.46	12.14	0.38	0.027	4384	5
2	4	5	8.08	7.84	15.40	7.74	7.67	7.62	7.57	7.54	7.50	12.56	0.34	0.022	5228	4
2	3	15	8.05	7.79	14.77	7.69	7.64	7.59	7.55	7.51	7.49	11.89	0.30	0.020	5202	3
1	2	16	8.07	7.82	14.87	7.73	7.66	7.60	7.57	7.53	7.51	12.15	0.31	0.021	5216	2
1	1	14	8.03	7.74	14.61	7.65	7.59	7.55	7.51	7.47	7.45	12.07	0.29	0.020	5361	1